

# SAFETY DATA SHEET



## TOMPS Polyurethane Fast Cast A - SLOW

### 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name: POLYURETHANE FAST CAST A - SLOW  
Company: TOMPS Ltd  
220 New Road  
Sutton Bridge  
PE12 9QE  
advice@tomps.com  
Telephone 0845 658 6677  
Fax 0845 658 5329

### 2 HAZARDS IDENTIFICATION

Main hazards No Significant Hazard

### 3 . COMPOSITION / INFORMATION ON INGREDIENTS

#### Hazardous ingredients

Conc.	CAS EINECS	Symbols/Risk phrases
1,4-Butanediol 1 - 30%	110-63-4 203-786-5	Xn; R22

### 4. FIRST AID MEASURES

**Skin contact** May cause irritation to skin. Wash off immediately with plenty of soap and water. Remove contaminated clothing. Seek medical attention if irritation or symptoms persist.

**Eye contact** May cause irritation to eyes. Rinse immediately with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if irritation or symptoms persist.

**Inhalation** May cause irritation to mucous membranes. Move the exposed person to fresh air.

**Ingestion** May cause irritation to mucous membranes. DO NOT INDUCE VOMITING. Seek medical attention if irritation or symptoms persist.

## TOMPS Polyurethane Fast Cast Part A - SLOW

Revision 1  
Revision date 8-8-2008  
Page 1

# SAFETY DATA SHEET



## 5. FIRE FIGHTING MEASURES

Extinguishing media	Use extinguishing media appropriate to the surrounding fire conditions.
Fire hazards	Burning produces irritating, toxic and obnoxious fumes.
Protective equipment	Wear suitable respiratory equipment when necessary.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions	Ensure adequate ventilation of the working area.
Environmental precautions	Do not allow product to enter drains. Prevent further spillage if safe.
Clean up methods	Absorb with inert, absorbent material. Sweep up. Transfer to suitable, labelled containers for disposal. Clean spillage area thoroughly with plenty of water.

## 7. HANDLING AND STORAGE

Handling	Avoid contact with eyes and skin. Ensure adequate ventilation of the working area. Adopt best Manual Handling considerations when handling, carrying and dispensing.
Storage	Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in correctly labelled containers.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering measures	Ensure adequate ventilation of the working area.
Hand protection	Chemical resistant gloves (PVC)
Eye protection	In case of splashing, wear: Approved safety goggles.
Protective equipment	Wear protective clothing.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Description Liquid.  
Colour Off white.  
Odour Slight.  
Relative density 1.04  
Viscosity 2200 mPa.s (25°C)

## TOMPS Polyurethane Fast Cast Part A - SLOW

Revision 1  
Revision date 8-8-2008  
Page 2

# SAFETY DATA SHEET



## 10. STABILITY AND REACTIVITY

Stability Stable under normal conditions.

## 11. TOXICOLOGICAL INFORMATION

## 12. ECOLOGICAL INFORMATION

## 13. DISPOSAL CONSIDERATIONS

General information Dispose of in compliance with all local and national regulations.

## 14. TRANSPORT INFORMATION

Further information The product is not classified as dangerous for carriage.

## 15. REGULATORY INFORMATION

Risk phrases NSH - No Significant Hazard.

## 16. OTHER INFORMATION

Text of risk phrases in Section 3.

R22 - Harmful if swallowed.

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such

## TOMPS Polyurethane Fast Cast Part A - SLOW