



SAFETY DATA SHEET
ANTIFOULING PAINT

Page 1
Issued: 26/02/2003
Revision No: 1

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

Product name: ANTIFOULING PAINT
Company name: C W Wastnage Ltd
8 Springfield Road
Springfield Industrial Estate
Burnham on Crouch
Essex
CM0 8UA
United Kingdom
Tel: +44 (0) 1621 785 173
Fax: +44 (0) 1621 785 393
Emergency tel: +44 (0) 1621 785 173

2. COMPOSITION / INFORMATION ON INGREDIENTS

3. HAZARDS IDENTIFICATION

Main hazards: Flammable. Harmful if swallowed. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Harmful: may cause lung damage if swallowed.

4. FIRST AID MEASURES (SYMPTOMS)

Skin contact: There may be mild irritation at the site of contact.
Eye contact: There may be irritation and redness.
Ingestion: There may be vomiting.

4. FIRST AID MEASURES (ACTION)

Skin contact: Wash immediately with plenty of soap and water.
Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion: Give 1 cup of water to drink every 10 minutes. Do not induce vomiting. Consult a doctor.
Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

5. FIRE-FIGHTING MEASURES

Extinguishing media: Dry chemical powder. Alcohol or polymer foam. Carbon dioxide.
Exposure hazards: Flammable.
Protection of fire-fighters: Wear protective clothing to prevent contact with skin and eyes.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions: Refer to section 8 of SDS for personal protection details.
Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.
Clean-up procedures: Contain spillage with sand or earth, sweep up and dispose of in accordance with a recognised method of waste disposal.

[cont...]

SAFETY DATA SHEET
ANTIFOULING PAINT**7. HANDLING AND STORAGE**

- Handling requirements:** Ensure there is sufficient ventilation of the area.
- Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition.
- Suitable packaging:** Must only be kept in original packaging.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION**Occupational exposure limits**

- TWA (8 hr exposure limit):** 100 (OES)
- Engineering measures:** Ensure there is sufficient ventilation of the area.
- Respiratory protection:** Gas/vapour filter, type A: organic vapours (EN141).
- Hand protection:** Nitrile gloves. Viton gloves.
- Eye protection:** Safety goggles.
- Skin protection:** Protective clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

- State:** Liquid
- Odour:** Aromatic
- Viscosity:** Non-viscous
- Viscosity value:** 6.0
- Viscosity test method:** Kinematic viscosity in 10-6 m²/s at 40°C (ISO 3104/3105)
- Boiling point/range°C:** 200
- Flash point°C:** 42
- Autoflammability°C:** >200
- Relative density:** 1.8

10. STABILITY AND REACTIVITY

- Stability:** Stable at room temperature.
- Conditions to avoid:** Sources of ignition.
- Materials to avoid:** Oxidising agents. Acids.
- Haz. decomp. products:** In combustion emits toxic fumes of carbon dioxide.

11. TOXICOLOGICAL INFORMATION

- Chronic toxicity:** Danger of cumulative effects if swallowed.
- Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

12. ECOLOGICAL INFORMATION

- Mobility:** Volatile. Insoluble in water.
- Persistence and degradability:** Biodegradable.
- Bioaccumulative potential:** Bioaccumulation potential.
- Other adverse effects:** Toxic to aquatic organisms. Toxic to soil-based organisms. Toxic to flora.

SAFETY DATA SHEET
ANTIFOULING PAINT

13. DISPOSAL CONSIDERATIONS

Disposal operations: Disposal in accordance with local authority regulations.
R1 Solvent reclamation/regeneration.

Disposal of packaging: Dispose of as normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

14. TRANSPORT INFORMATION

ADR / RID

| | |
|-----------------------------|--------------------------------|
| UN no: 1263 | ADR Class: 3 |
| Packing group: III | Classification code: F1 |
| Hazard ID no: 30 | Labelling: 3 |
| Shipping name: PAINT | |

IMDG / IMO

| | |
|----------------------------|---------------------|
| UN no: 1263 | Class: 3 |
| Packing group: III | EmS: 3-05 |
| Marine pollutant: . | Labelling: 3 |

IATA / ICAO

| | |
|---------------------------|--|
| UN no: 1263 | Class: 3 |
| Packing group: III | Packing instructions: 309(P&CA); 310(PAO) |
| Labelling: 3 | |

15. REGULATORY INFORMATION

Hazard symbols: Dangerous for the environment.
Harmful.



Risk phrases: R10: Flammable.
R22: Harmful if swallowed.
R43: May cause sensitisation by skin contact.
R51/53: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65: Harmful: may cause lung damage if swallowed.

Safety phrases: S24: Avoid contact with skin.
S29: Do not empty into drains.
S37: Wear suitable gloves.

Note: The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to

SAFETY DATA SHEET
ANTIFOULING PAINT

the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

16. ADDITIONAL INFORMATION

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.