

CAB-O-SIL® H-5



CAB-O-SIL® H-5 untreated fumed silica is a synthetic, amorphous, colloidal silicon dioxide that is generally regarded as unique in industry because of its unusual particle characteristics. CAB-O-SIL fumed silica's extremely small particle size, its enormous surface area, its high purity, and its chain-forming tendencies set it apart in a class of its own. CAB-O-SIL fumed silica is a light, fluffy powder that is white in appearance and is used in many applications and a variety of industries.

Product Form

Powder

Typical Properties

B.E.T. Surface Area	300 m ² /g
pH (4% aqueous slurry)	3.7–4.3
325 Mesh Residue (44 microns)	0.02% max.
Bulk Density* (Pour Density)	3.0 lb/ft ³ max. (50 g/l Tap Density)
Loss on Heating*	< 1.5% max.
Loss on Ignition* (@ 1000°C)	< 2.5 wt. %
Specific Gravity Wt. per gallon	2.2 g/cm ³ 18.3 lb
Refractive Index	1.46
X-ray Form	Amorphous
Assay (% SiO ₂)	> 99.8
Average Particle (Aggregate) Length	0.2–0.3 microns

*At time of packaging.



Functions

Rheology Control
Reinforcement
Free Flow
Suspension
Adsorbant

Applications

Adhesives
Coatings
Composites
Cosmetics
Foods
Inks
Pharmaceuticals
Powder Coatings
Sealants
Silicone Rubber Systems

Packaging Options

CAB-O-SIL® fumed silicas are packaged in color-coded, multi-wall Kraft paper bags. Grade H-5 is packaged in Europe in 10-kg bags. The bags are unitized and sized to provide product protection, facilitate efficient handling, and maximize payloads. Specific information regarding standard and custom packaging may be obtained by contacting a sales service representative at the Cabot Corporation office in your region.

MSDS

A Material Safety Data Sheet for this product may be obtained by contacting the Cabot Corporation office in your region or visiting our website.

This information is provided as a convenience and for informational purposes only. No guarantee or warranty as to this information, or any product to which it relates, is given or implied. This information may contain inaccuracies, errors or omissions and CABOT DISCLAIMS ALL WARRANTIES EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AS TO (i) SUCH INFORMATION, (ii) ANY PRODUCT OR (iii) INTELLECTUAL PROPERTY INFRINGEMENT. In no event is Cabot responsible for, and Cabot does not accept and hereby disclaims liability for, any damages whatsoever in connection with the use of or reliance on this information or any product to which it relates.

USA
Cabot Corporation
157 Concord Road
Billerica, MA 01821-7001
USA
Tel: (978) 663-3455 or
(800) 462-2313
Fax: (978) 670-7035

GERMANY
Cabot GmbH
Kronenstrasse 2
79618 Rheinfelden
Germany
Tel: (49) 7623 707 0
Fax: (49) 7623 707 53

MALAYSIA
Cabot Specialty Chemicals, Inc.
Level 21, MNI Tower 2
No. 11, Jalan Pinang
50450 Kuala Lumpur
Malaysia
Tel: (60-3) 2164-8352
Fax: (60-3) 2162-0253

BRAZIL
Cabot Brasil Industria e
Comércio Ltda.
Av. João Castaldi, 88
04517-900, São Paulo, SP
Brazil
Tel: (55-11) 5091-8300
Fax: (55-11) 5542-6037