



SPECIALTY PRODUCTS CO.

1691 California Ave.

TEL: +1 951-479-0179

www.specialtyproductsco.com

Corona, CA 92881 USA

FAX: +1 951-273-3918

info@specialtyproductsco.com

GOLDEN WAX[®] LIQUID 2

A Mold Release Agent that Cleans as it Waxes

PRODUCT DESCRIPTION

Golden Wax[®] Liquid 2 is a mold release agent specifically formulated for use in the manufacture of reinforced fiberglass products. Because of its unique solvent carrier, **Golden Wax[®] Liquid 2** removes old wax build-up, while forming a durable wax surface. This cleaning ability, while reducing the wax build-up, allows molds to be kept in production longer between cleanings, thus saving valuable man-hours.

ADVANTAGES

- It cleans the mold surface as it waxes, minimizing wax build-up and increasing mold life.
- Goes on easily and fast, reducing labor.
- Provides a durable releasing film.
- Simple hand buffing without the use of equipment.
- Provides highly lustrous and reproducible parts.
- Can be used for smooth as well as textured mold surfaces.

APPLICATION

MIX BEFORE USE. Because of this product's fluid nature, an easier and faster application to the mold can be made. **Golden Wax[®] Liquid 2**, when applied, yields a thinner wax layer than that of paste wax. Therefore, it can be spread easier and buffed more quickly to a high luster preventing potential wax build-up on any mold surface.

New Molds: Clean the mold surface using a solvent cleaner such as **KantStik[®] Mold Cleaner**. For best release results, it is strongly recommended to use a sealer such as **KantStik[®] Sealer** to fill in micropores and establish a styrene resistant barrier. Apply **Golden Wax[®] Liquid 2** to a cleaned mold by wiping on with a clean cloth, or by spray or brush which may be preferred under certain conditions. Once the wax film haze has formed, buff with a fresh clean cloth to a high gloss.

Conditioned Molds: When applying to a mold that had been previously waxed, the surface should be rubbed vigorously to remove the old wax while simultaneously forming a new wax surface. As the surface begins to dry, another clean cloth should be used to buff the surface until a high gloss is provided.

If the mold surface is grained textured or sand-like with a rough texture, it may be advantageous to apply **Golden Wax[®] Liquid 2** by brush or spray. This will better facilitate **Golden Wax[®] Liquid 2's** penetration into these small crevices, assuring good surface reproduction and minimizing build-up. Buffing may be done with a cloth or soft bristled brush.

AVAILABILITY

Available in cases of 4x1-gallon containers, 5-gallon pails and 55-gallon drums.

SAFETY

As with any other flammable product, **Golden Wax[®] Liquid 2** must be carefully used and kept away from any open flames or sources of heat and ignition. Containers should be kept closed when not in use and stored in a dry, cool area. For more information, please refer to our Material Safety Data Sheet.